

Symbolic Unfolding Of Time Petri Nets



Collaboration INRIA/Distribcom & CNRS/IRCCyN

March 22, 2012



Introduction

- ▶ Objectives:
 - ▶ Modeling and analysis of **concurrent timed** systems,
 - ▶ Explicit the causality between events and **preserve** concurrency,
 - ▶ Infer constraints on the value of **parameters**.
- ▶ Applications in the Distribcom group:
 - ▶ Diagnosis (root cause analysis),
 - ▶ Causality-based testing,
 - ▶ QoS evaluation,
 - ▶ Concurrent semantics of timed languages (e.g. ORC).
- ▶ Main contribution:
 - ▶ Unfoldings of TPNs are not TPNs: new idea of symbolic unfoldings and conditions for having finite prefixes (a ten years old problem).



Petri nets and branching processes





Petri nets and branching processes





Petri nets and branching processes





Petri nets and branching processes





Petri nets and branching processes



Petri nets and branching processes





Petri nets and branching processes





The **unfolding** of the Petri net is the **greatest** branching process.



Time Petri nets (TPN) and time processes





Time Petri nets (TPN) and time processes





Time Petri nets (TPN) and time processes





Time Petri nets (TPN) and time processes





Time Petri nets (TPN) and time processes





Time Petri nets (TPN) and time processes





Time Petri nets (TPN) and time processes





From time processes to time branching processes





From time processes to time branching processes





From time processes to time branching processes





From time processes to time branching processes





From time processes to time branching processes



From time processes to time branching processes





From time processes to time branching processes





The **symbolic unfolding** of the time Petri net is the **union** of all time branching processes.

$$\left\{ \begin{array}{l} \theta(\perp) = 0, \\ \theta(e_1) = 0, \\ \theta(e_2) = 2, \\ \theta(e_3) = 2, \\ \theta(e_4) = +\infty \end{array} \right. \quad \text{or} \quad \left\{ \begin{array}{l} \theta(\perp) = 0, \\ 0 \leq \theta(e_1), \\ 1 \leq \theta(e_2) \leq 2, \\ \theta(e_3) = +\infty, \\ \theta(e_4) = \max(\theta(e_1), \theta(e_2)) \end{array} \right.$$

Locality



Locality



Conflicts with **urgency** break the locality of the firing rule.

Valid Time Branching Processes

We define the following constraints for a time labeling θ to be **valid**:

The transition fires in its interval

$$\left[\theta(e) \neq \infty \wedge \theta(e) - \text{TOE}(e) \in [\text{eft}(l(e)), \text{lft}(l(e))] \right]$$

where $\bullet e$ is the set of preconditions of e , $l(e)$ is the transition labeling e ,
 $\text{TOE}(e) = \max(\theta(b) \mid b \in \bullet e)$.

Valid Time Branching Processes

We define the following constraints for a time labeling θ to be **valid**:

The transition fires in its interval

$$\left[\theta(e) \neq \infty \wedge \theta(e) - \text{TOE}(e) \in [\text{eft}(l(e)), \text{lft}(l(e))] \right.$$

... and no transition in direct conflict fires

$$\left. \wedge \forall e' \text{ conf } e, \theta(e') = \infty \right]$$

where $\bullet e$ is the set of preconditions of e , $l(e)$ is the transition labeling e ,
 $\text{TOE}(e) = \max(\theta(b) \mid b \in \bullet e)$.

Valid Time Branching Processes

We define the following constraints for a time labeling θ to be **valid**:

The transition fires in its interval

$$\left[\theta(e) \neq \infty \wedge \theta(e) - \text{TOE}(e) \in [\text{eft}(l(e)), \text{lft}(l(e))] \right]$$

... and no transition in direct conflict fires

$$\wedge \forall e' \text{ conf } e, \theta(e') = \infty \Big]$$

The transition does not fire because

... one of its precondition was never produced

$$\vee \left[\theta(e) = \infty \wedge \exists b \in \bullet e, \theta(\bullet b) = \infty \right]$$

where $\bullet e$ is the set of preconditions of e , $l(e)$ is the transition labeling e ,
 $\text{TOE}(e) = \max(\theta(b) \mid b \in \bullet e)$.

Valid Time Branching Processes

We define the following constraints for a time labeling θ to be **valid**:

The transition fires in its interval

$$\left[\theta(e) \neq \infty \wedge \theta(e) - \text{TOE}(e) \in [\text{eft}(l(e)), \text{lft}(l(e))] \right]$$

... and no transition in direct conflict fires

$$\wedge \forall e' \text{ conf } e, \theta(e') = \infty \Big]$$

The transition does not fire because

... one of its precondition was never produced



$$\vee \left[\theta(e) = \infty \wedge \exists b \in \bullet e, \theta(\bullet b) = \infty \right]$$

... a directly conflicting transition fires before



$$\vee \left[\theta(e) = \infty \wedge \exists e' \text{ conf } e \wedge \theta(e') \neq \infty \wedge \theta(e') - \text{TOE}(e) \leq \text{lft}(l(e)) \right]$$

where $\bullet e$ is the set of preconditions of e , $l(e)$ is the transition labeling e ,
 $\text{TOE}(e) = \max(\theta(b) \mid b \in \bullet e)$.


Infinite unfoldings and finite prefixes




Infinite unfoldings and finite prefixes




Infinite unfoldings and finite prefixes




► $I(\text{CutA}) = I(\text{CutB}) = \{p_1, p_2\}$




Infinite unfoldings and finite prefixes




- ▶ $I(\text{CutA}) = I(\text{CutB}) = \{p_1, p_2\}$
- ▶ $I(b_1) = I(b_6) = p_1$




Infinite unfoldings and finite prefixes




- ▶ $I(\text{CutA}) = I(\text{CutB}) = \{p_1, p_2\}$
- ▶ $I(b_1) = I(b_6) = p_1$
- ▶ $\text{age}(b_1) = \min\{5, \max\{\theta(\bullet b_1), \theta(\bullet b_2)\} - \theta(\bullet b_1)\} = 0$




Infinite unfoldings and finite prefixes




- ▶ $I(\text{CutA}) = I(\text{CutB}) = \{p_1, p_2\}$
- ▶ $I(b_1) = I(b_6) = p_1$
- ▶ $\text{age}(b_1) = \min\{5, \max\{\theta(\bullet b_1), \theta(\bullet b_2)\} - \theta(\bullet b_1)\} = 0$
- ▶ $\text{age}(b_6) = \min\{5, \max\{\theta(\bullet b_6), \theta(\bullet b_7)\} - \theta(\bullet b_6)\} = 0 = \text{age}(b_1)$




Infinite unfoldings and finite prefixes




- ▶ $I(\text{CutA}) = I(\text{CutB}) = \{p_1, p_2\}$
- ▶ $I(b_1) = I(b_6) = p_1$
- ▶ $\text{age}(b_1) = \min\{5, \max\{\theta(\bullet b_1), \theta(\bullet b_2)\} - \theta(\bullet b_1)\} = 0$
- ▶ $\text{age}(b_6) = \min\{5, \max\{\theta(\bullet b_6), \theta(\bullet b_7)\} - \theta(\bullet b_6)\} = 0 = \text{age}(b_1)$
- ▶ Similarly, $I(b_2) = I(b_7) = p_2$ and $\text{age}(b_2) = \text{age}(b_7) = 0$




Infinite unfoldings and finite prefixes




- ▶ $I(\text{CutA}) = I(\text{CutB}) = \{p_1, p_2\}$
- ▶ $I(b_1) = I(b_6) = p_1$
- ▶ $\text{age}(b_1) = \min\{5, \max\{\theta(\bullet b_1), \theta(\bullet b_2)\} - \theta(\bullet b_1)\} = 0$
- ▶ $\text{age}(b_6) = \min\{5, \max\{\theta(\bullet b_6), \theta(\bullet b_7)\} - \theta(\bullet b_6)\} = 0 = \text{age}(b_1)$
- ▶ Similarly, $I(b_2) = I(b_7) = p_2$ and $\text{age}(b_2) = \text{age}(b_7) = 0$
- ▶ *CutA* and *CutB* are **equivalent**




Infinite unfoldings and finite prefixes





- ▶ $I(CutA) = I(CutB) = \{p_1, p_2\}$
- ▶ $I(b_1) = I(b_6) = p_1$
- ▶ $age(b_1) = \min\{5, \max\{\theta(\bullet b_1), \theta(\bullet b_2)\} - \theta(\bullet b_1)\} = 0$
- ▶ $age(b_6) = \min\{5, \max\{\theta(\bullet b_6), \theta(\bullet b_7)\} - \theta(\bullet b_6)\} = 0 = age(b_1)$
- ▶ Similarly, $I(b_2) = I(b_7) = p_2$ and $age(b_2) = age(b_7) = 0$
- ▶ *CutA* and *CutB* are **equivalent**
- ▶ e_5 and e_6 are **cutoff** events



Parametric TPNs (PTPNs)



Parametric TPNs (PTPNs)



The **symbolic unfolding** of the PTPN is the **union** of all time branching processes for all feasible **parameter valuations**.

$$\left\{ \begin{array}{l} \theta(\perp) = 0, \\ 0 \leq \theta(e_1), \\ \mathbf{a} \leq \theta(e_2) \leq \mathbf{b}, \\ \theta(e_3) = \theta(e_1) + 2, \\ \theta(e_3) \leq \theta(e_2) \\ \theta(e_4) = +\infty \end{array} \right. \quad \text{or} \quad \left\{ \begin{array}{l} \theta(\perp) = 0, \\ 0 \leq \theta(e_1), \\ \mathbf{a} \leq \theta(e_2) \leq \mathbf{b}, \\ \theta(e_3) = +\infty, \\ \theta(e_4) = \max(\theta(e_1), \theta(e_2)) \end{array} \right.$$

References I



Franck Cassez, Thomas Chatain, and Claude Jard.

Symbolic Unfoldings for Networks of Timed Automata.

In *4th Int. Symp. on Automated Technology for Verification and Analysis (ATVA'06)*, volume 4218 of *Lecture Notes in Computer Science*, pages 307–321, Beijing, China, October 2006. Springer.



T. Chatain and C. Jard.

Complete finite prefixes of symbolic unfoldings of safe time petri nets.

In *Proceedings of ICATPN*, volume 4024 of *LNCS*, pages 125–145. Springer, 2006.



B. Grabiec and C. Jard.

Unfolding of networks of automata and their application in supervision.

In *Proceedings of NOTERE*, 2009.

References II



B. Grabiec, L.-M. Traonouez, C. Jard, D. Lime, and O. H. Roux.
Diagnosis using unfoldings of parametric time Petri nets.
In *Proceedings of FORMATS*, LNCS, Vienna, Austria, September 2010. Springer.



L.-M. Traonouez, B. Grabiec, C. Jard, D. Lime, and O. H. Roux.
Symbolic unfolding of parametric swpns.
In *Proceedings of ATVA*, LNCS, Singapore, September 2010. Springer.